



MeterBoxesDirect.co.uk



IP66 ELECTRICAL ENCLOSURE BY TRICEL

540x270x170mm Surface

FIRE RETARDANT TO BS 476, PART 7, 1997, CLASS 2

STOCK CODE: 105019



IP66 ELECTRICAL ENCLOSURE BY TRICEL

540x270x170mm Surface

Fire retardant to BS 476, Part 7, 1997, Class 2

STOCK CODE: 105019



BUY ONLINE NOW

Compliant with IEC 62208 (2011) - Empty enclosures for low-voltage switchgear and control gear assemblies.

DIMENSIONS

Internal dimensions: 522mm high x 252mm wide x 156mm deep

Outside dimensions: 540mm high x 270mm wide x 170mm deep

SPECIFICATIONS

- IP66 rating (EN 60529) suitable for electrical installations
- Certification of compliance with IEC 62208 (2011)
- Suitable for indoor or outdoor use
- Constructed from fire retardant GRP – Glass Reinforced Polymer.
- Fire retardant to BS 476, Part. 7, 1997, Class 2.
- Will not corrode, weather resistant.
- Complete with hinges, lock and key.
- Supplied with backboard, ready to be assembled.
- Suitable for meters, electrical equipment, compressors, CCTV, industrial automation, marine etc.

Note: any electrical equipment fitted to Tricel enclosures must be completed by an appropriately qualified person.



IP66 Electrical Meter Box



* Approximate dimensions.

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

Tricel (Gloucester) Ltd. - Fox House, Stonedale Road, Stonehouse, Gloucestershire, GL10 3SA, United Kingdom.

Tel: 0844 809 4206 | Email: onlinesales@meterboxesdirect.co.uk | www.meterboxesdirect.co.uk

IP66 ELECTRICAL ENCLOSURE BY TRICEL

540x270x170mm Surface

Fire retardant to BS 476, Part 7, 1997, Class 2

STOCK CODE: 105019



BUY ONLINE NOW

ASSEMBLY

FITTING THE BASE PLATE:



1. To fit the base to the enclosure, screw down all six screws into the enclosure using a Phillips head screwdriver, ensuring that they are tightly screwed in.



2. Fit the top cover to the enclosure by screwing all six screws down into the enclosure using a flat head screwdriver.